

LED SPOT LIGHT ANTI-GLARE

Data Sheet

NEWPOWER®

ITEM NO: 103105

LED SPOT LIGHT ANTI-GLARE RECESSED MOVING



CAPTION	THE VALUE
Rated wattage	7 W
Rated current	55-107 mA
Rated Voltage	100-240V
Power Factor	50/60 Hz
Displacement Factor	0.7
Rated lumens	560 Lm
Efficiency	80 Lm/w
Lumen Maintenance	6000h
Beam Angle	38°
Color temperature	6500 K
Consistency sdcn	<6
CRI	>80
Rated Lifetime	15000 h
Switch cycle	7500
Ta	40 °c
Cutout	75 mm
Width	85 mm
Height	47 mm
weight	32 g
Dimming	No
Main color of the luminaire	White

Areas of application:

- > General indoor illumination
- > Decorative illumination
- > Private living areas


Super protection:

- > It is made of very safe materials, so it is environmentally friendly
- Provides flexibility in installation and ease of installation.

Usage:

- > Spotlight lighting for lighting interior ceilings perfectly, which is suitable for gypsum and concrete lamps, so it can be placed in rooms of the house, companies, or hotels.

1. Energy Savings
2. Eco-Friendly
3. High Brightness
4. Flexible Features
5. Lights Up Instantly
6. Less Heat Dissipation
7. Shock-Resistant



75mm

