

LED SPOT LIGHT ANTI-GLARE

Data Sheet

NEWPOWER®

ITEM NO: 103110

LED SPOT LIGHT ANTI-GLARE RECESSED MOVING



CAPTION	THE VALUE
Rated wattage	7 W
Rated current	55-107 mA
Rated Voltage	100-240V
Power Factor	50/60 Hz
Displacement Factor	0.7
Rated lumens	560 Lm
Efficiency	80 Lm/w
Lumen Maintenance	6000h
Beam Angle	38°
Color temperature	4000 K
Consistency sdcn	<6
CRI	>80
Rated Lifetime	15000 h
Switch cycle	7500
Ta	40 °c
Cutout	75 mm
Width	85 mm
Height	47 mm
weight	32 g
Dimming	No
Main color of the luminaire	White / Black

Areas of application:

- > General indoor illumination
- > Decorative illumination
- > Private living areas


Super protection:

- > It is made of very safe materials, so it is environmentally friendly
- Provides flexibility in installation and ease of installation.

Usage:

- > Spotlight lighting for lighting interior ceilings perfectly, which is suitable for gypsum and concrete lamps, so it can be placed in rooms of the house, companies, or hotels.

- »
1. Energy Savings
 2. Eco-Friendly
 3. High Brightness
 4. Flexible Features
 5. Lights Up Instantly
 6. Less Heat Dissipation
 7. Shock-Resistant
- «



75mm

