## **DOWN LIGHT FROSTED**

Data Sheet -



# **ITEM NO: 103029**

RECESSED FROSTED FACE **DOWN LIGHT - 4.8 W** 



| CAPTION                     | THE VALUE  |
|-----------------------------|------------|
| Rated wattage               | 4.8 W      |
| Rated current               | 0.03 mA    |
| Rated Voltage               | 220-240V   |
| Power Factor                | 50/60 Hz   |
| Displacement Factor         | 0.8        |
| Rated lumens                | 410 Lm     |
| Efficiency                  | 85.41 Lm/w |
| Lumen Maintenance           | 6000h      |
| Beam Angle                  | 100°       |
| Color temperature           | 3000 k     |
| Consistency sdcm            | <6         |
| CRI                         | >80        |
| Rated Lifetime              | 25000 h    |
| Switch cycle                | 20000      |
| Та                          | -10~45°c   |
| Cutout                      | 70 ф       |
| Width                       | 90 mm      |
| Height                      | 33 mm      |
| weight                      | 240 g      |
| Dimming                     | No         |
| Main color of the luminaire | White      |

### **Areas of application:**

- General indoor illumination
- Decorative illumination
- Private living areas

#### **Super protection:**

> It is made of very safe materials, so it is environmentally friendly Provides flexibility in installation and ease of installation.

- 1. Energy Savings
- 2. Eco-Friendly
- 3. High Brightness
- 4. Flexible Features
- 5. Lights Up Instantly
- 6. Less Heat Dissipation
- 7. Shock-Resistant

"

#### LIGHT DISTRIBUTION CURVE

































