DOWN LIGHT HYBRID

Data Sheet



ITEM NO: 103042

RECESSED HYBRID DOWN LIGHT

6 W



| CAPTION | THE VALUE |
|-----------------------------|-----------|
| Rated wattage | 6 W |
| Rated current | 0.050 mA |
| Rated Voltage | 220-240V |
| Power Factor | 50/60 Hz |
| Displacement Factor | 0.9 |
| Rated lumens | 450 Lm |
| Efficiency | 75 Lm/w |
| Lumen Maintenance | 6000h |
| Beam Angle | 120° |
| Color temperature | 4000 k |
| Consistency sdcm | <3 |
| CRI | >80 |
| Rated Lifetime | 20000 h |
| Switch cycle | 15000 |
| Та | 40 °c |
| Cutout | 70 mm |
| Width | 90 mm |
| Height | 27.5 mm |
| weight | 65 g |
| Dimming | No |
| Main color of the luminaire | White |
| | |

Areas of application:

- General indoor illumination
- Decorative illumination
- Private living areas

Super protection:

> It is made of very safe materials, so it is environmentally friendly Provides flexibility in installation and ease of installation.

- 1. Energy Savings
- 2. Eco-Friendly
- 3. High Brightness
- 4. Flexible Features
- 5. Lights Up Instantly 6. Less Heat Dissipation
- 7. Shock-Resistant

LIGHT DISTRIBUTION CURVE

































