DOWN LIGHT HYBRID

Data Sheet -



ITEM NO: 103040

RECESSED HYBRID DOWN LIGHT

6W



CAPTION	THE VALUE
Rated wattage	6 W
Rated current	0.050 mA
Rated Voltage	220-240V
Power Factor	50/60 Hz
Displacement Factor	0.9
Rated lumens	450 Lm
Efficiency	75 Lm/w
Lumen Maintenance	6000h
Beam Angle	120°
Color temperature	6500 k
Consistency sdcm	<3
CRI	>80
Rated Lifetime	20000 h
Switch cycle	15000
Та	40 °c
Cutout	70 mm
Width	90 mm
Height	27.5 mm
weight	65 g
Dimming	No
Main color of the luminaire	White

Areas of application:

- > General indoor illumination
- > Decorative illumination
- Private living areas

Super protection:

> It is made of very safe materials, so it is environmentally friendly Provides flexibility in installation and ease of installation.


1. Energy Savings

"

- 2. Eco-Friendly
- 3. High Brightness
- 4. Flexible Features
- 5. Lights Up Instantly
- 6. Less Heat Dissipation
- 7. Shock-Resistant

"

LIGHT DISTRIBUTION CURVE

































rkot Dotail Sto

Hot

School

Hospital