# **DOWN LIGHT HYBRID**

Data Sheet



# **ITEM NO: 103053**

SURFACE HYBRID DOWN LIGHT 30 W



CAPTION	THE VALUE
Rated wattage	30 W
Rated current	0.2 A
Rated Voltage	220-240V
Power Factor	50/60 Hz
Displacement Factor	0.9
Rated lumens	2400 Lm
Efficiency	80 Lm/w
Lumen Maintenance	6000h
Beam Angle	120°
Color temperature	3000 k
Consistency sdcm	<6
CRI	>80
Rated Lifetime	20000 h
Switch cycle	15000
Та	-20~45°c
Cutout	NA
Width	230*55 mm
Height	225 mm
weight	0.5 kg
Dimming	No
Main color of the luminaire	White & Black

## Areas of application:

- General indoor illumination
- Decorative illumination
- Private living areas

### **Super protection:**

> It is made of very safe materials, so it is environmentally friendly Provides flexibility in installation and ease of installation.

- 1. Energy Savings
- 2. Eco-Friendly
- 3. High Brightness
- 4. Flexible Features
- 5. Lights Up Instantly
- 6. Less Heat Dissipation
- 7. Shock-Resistant

#### LIGHT DISTRIBUTION CURVE































