

ITEM NO: 103052

SURFACE HYBRID DOWN LIGHT

30 W



| CAPTION | THE VALUE |
|-----------------------------|---------------|
| Rated wattage | 30 W |
| Rated current | 0.2 A |
| Rated Voltage | 220-240V |
| Power Factor | 50/60 Hz |
| Displacement Factor | 0.9 |
| Rated lumens | 2400 Lm |
| Efficiency | 80 Lm/w |
| Lumen Maintenance | 6000h |
| Beam Angle | 120° |
| Color temperature | 6500 k |
| Consistency sdcn | <6 |
| CRI | >80 |
| Rated Lifetime | 20000 h |
| Switch cycle | 15000 |
| Ta | -20~45°C |
| Cutout | NA |
| Width | 230*55 mm |
| Height | 225 mm |
| weight | 0.5 kg |
| Dimming | No |
| Main color of the luminaire | White & Black |

Areas of application:

- > General indoor illumination
- > Decorative illumination
- > Private living areas

Super protection:

- > It is made of very safe materials, so it is environmentally friendly
- Provides flexibility in installation and ease of installation.

1. Energy Savings
2. Eco-Friendly
3. High Brightness
4. Flexible Features
5. Lights Up Instantly
6. Less Heat Dissipation
7. Shock-Resistant

LIGHT DISTRIBUTION CURVE

