

DOWN LIGHT HYBRID

Data Sheet

NEWPOWER®

ITEM NO: 103052

SURFACE HYBRID DOWN LIGHT

30 W



CAPTION	THE VALUE
Rated wattage	30 W
Rated current	0.2 A
Rated Voltage	220-240V
Power Factor	50/60 Hz
Displacement Factor	0.9
Rated lumens	2400 Lm
Efficiency	80 Lm/w
Lumen Maintenance	6000h
Beam Angle	120°
Color temperature	6500 k
Consistency sdcn	<6
CRI	>80
Rated Lifetime	20000 h
Switch cycle	15000
Ta	-20~45°C
Cutout	NA
Width	230*55 mm
Height	225 mm
weight	0.5 kg
Dimming	No
Main color of the luminaire	White & Black

Areas of application:

- > General indoor illumination
- > Decorative illumination
- > Private living areas

Super protection:

- > It is made of very safe materials, so it is environmentally friendly
- Provides flexibility in installation and ease of installation.

- ”
1. Energy Savings
 2. Eco-Friendly
 3. High Brightness
 4. Flexible Features
 5. Lights Up Instantly
 6. Less Heat Dissipation
 7. Shock-Resistant
- “

LIGHT DISTRIBUTION CURVE

