

ITEM NO: 500031

UNDERGROUND UP-LIGHT 18W

BEAM ANGLE: 24°



Accessories



Installation Drawing

1



power line
input voltage

Dig a hole just a little bigger than hole cut size of the lamp.


2



plastic barrel
ground
cement paste
input voltage
hole wire

Put the power wire into plastic barrel and bury the plastic barrel with cement paste.


3



ground
plastic barrel
cement paste
input voltage
hole wire

Connect the power wire with the wire of lamp well.

4



cover of lamp
glass cover
light body
plastic barrel
input voltage
hole for wire

Input the glass cover to light body, and then use the screws and make the lamp cover with the lamp body tightly.

CAPTION

THE VALUE

MATERIAL	201SS COVER*ALU BODY
CHIP	BRIDGELUX
SIZE	200*90 MM
CUTOUT	185*90 MM
LED QUANTITY	18 PCS
RATED POWER	18 W
INPUT VOLTAGE	AC85 - 265
LIGHT COLOR	3000K
CRI	>80
BEAM ANGLE	24°
GLASS SURFACE TEMPERATURE	40°C
LED LIFETIME	>30000H
PROTECTION GRADE	IP65

Areas of application:

- General outdoor illumination

Super protection:

- It is made of very safe materials, so it is environmentally friendly
- Provides flexibility in installation and ease of installation.

